



GIVE YOUR HOME A BEAUTIFUL AND LASTING FINISH WITH

PARAMOUNT SHINE

ACRYLIC DISTEMPER

PRODUCT DESCRIPTION

Paramount Shine Super Acrylic Washable Distemper is an acrylic emulsion-based interior wall coating that provides a rich, silky-smooth, and durable finish. It comes in paste form in attractive, reusable plastic pails and is easily thinned with water. Suitable for use on cement, lime, brick, asbestos, and more, this coating is ideal for interior decoration of ceiling and wall surfaces. It is also washable with water or a mild soap solution and will acquire scrub resistance after 7 days. Shades are clean and bright, and there are pastel collections available.

SURFACE PREPARATION

PLASTER

It is essential that newly constructed masonry surfaces have a minimum curing period of 28 days before any further application. It is also recommended that a base coat of Paramount Shine Acrylic Distemper be applied before using interior Emulsion for optimal results.

CLEANING

The surface must be free from any dirt, oil, grease, and other impurities. All loose material should be removed using a scraper or a stiff wire brush. Any dampness on the wall should be treated accordingly.

FILLING CRACKS, HOLES, AND DENTS

For repairing cracks up to 3 mm, holes, and dents, mix Paramount Shine Wall Putty or white cement with fine sand in a 1:3 ratio. Then, put on a coat of Paramount Shine Interior Primer. Rub the area with emery paper no 320 to get a smooth and even finish. Wipe away any dust with a soft and dry cloth. Finally, paint the surface with diluted Paramount Shine Acrylic Distemper.



HANDLING AND STORAGE

Keep containers airtight during handling and storage to avoid loss of material. Store Paramount Shine Acrylic Distemper in a cool dry place and also protect it from extreme climatic conditions during storage, in transit, and at the site.

Packing Size Available

2kg, 5kg, 10kg, & 20kg

SAFETY

Please refer to the detailed MSDS of Paramount Shine Acrylic Distemper for detailed information on the safe handling of the product.

- Suitable for both interior and exterior surfaces
- Easy to clean up
- No need for primer coating
- Resistant to fading, chalking, and cracking
- Quick and easy to apply

ADDING COLOR TO YOUR SPACE FOR OVER A DECADE!



Corporate Office: Om Plaza, First Floor, 7-Krishna Vihar Govindpuri,
Sachin Tendulkar Marg, Gwalior (M.P.)-474011

Plant: TIWH, Purani Chawani, Gwalior



GIVE YOUR HOME A BEAUTIFUL
AND LASTING FINISH WITH
PARAMOUNT SHINE
ACRYLIC DISTEMPER

TECHNICAL SPECIFICATION

PROPERTY	TYPICAL
Consistency of Supply	A smooth silky paste
Surface to be Painted	Plaster, brickwork, asbestos cement sheets, concrete etc
Thinner to be Used	Water
Primer to be Used	Paramount Shine Wall Primer (Water Based)
Drying Time	Surface drying within 30 minutes, hard drying within 2-4 Hours. The above varies with atmospheric temperature and humidity
Coverage Capacity	120-140 Sq Ft per Kg per coat, 60-70 Sq Ft per Kg Double coat. This may vary depending upon the surface to be coated and shade used
Finish	Matt and Smooth

FEATURES

Durability:

Highly durable and can last up to 10 years with proper maintenance.

Weatherproof:

Weatherproof and provides protection against extreme weather conditions like heavy rains and strong sunshine.

Breathable:

It allows moisture to escape from the walls, reducing the risk of dampness and mildew.

Easy to clean:

It is water-resistant, thus, easy to clean and maintain.

**PROFESSIONAL SERVICE |
PREMIUM-QUALITY PAINT | AFFORDABLE**

APPLICATION PROCEDURE

CAUTIONS

- On a freshly coated surface, washing is permissible only after one week. Do not use synthetic detergents for washing.
- The above information is given for guidance only. It is true and accurate to the best of our knowledge. However, it is without any guarantee, since conditions of use are beyond our control.

APPLICATION

- Brush or Spray

**ADDING COLOR TO
YOUR SPACE FOR OVER
A DECADE!**

