



## CREATE A PERFECT FINISH WITH **PARAMOUNT SHINE** ACRYLIC EMULSION EXTERIOR

### PRODUCT DISCRIPTION

Paramount Shine Acrylic Emulsion – Exterior is a 100% pure acrylic emulsion that offers superb bacterial and UV resistance. It is a reliable and enduring coating, specifically formulated to bear the harsh weather conditions of high rain, high temperatures and high humidity. It can be used on a wide range of exterior surfaces such as cement plaster, masonry, concrete, asbestos sheet, POP Gypsum, etc.

### SURFACE PREPARATION

#### PLASTER

It is essential that newly constructed masonry surfaces have a minimum curing period of 28 days before any further application. It is also recommended that a base coat of Paramount Exterior Emulsion and exterior primer be applied before using Exterior Emulsion for optimal results.



#### CLEANING

The surface must be free from any dirt, oil, grease and other impurities. All loose material should be removed using a scraper or a stiff wire brush. Any dampness on the wall should be treated accordingly.



#### FILLING CRACKS, HOLES AND DENTS

For repairing cracks up to 3 mm, holes and dents, mix Paramount Shine Wall Putty or white cement with fine sand in a 1:3 ratio. If the interior surface or substrate is regularly exposed to moisture or dampness, ensure the repairs are done prior to application.



### PRECAUTION

Do not over-dilute or over-extend the brush. Stir Well Before Use.

### POST PAINTING CARE

For performance optimization – ensure proper washing and cleaning of structures at regular intervals.

### HANDLING AND STORAGE

Keep containers airtight during handling and storage to avoid loss of material. Store Paramount Shine Exterior Emulsion Paint in a cool dry place and also protect it from extreme climatic conditions during storage, in transit and at the site.

### SAFETY

Please refer to the detailed MSDS of Paramount Shine Acrylic Emulsion – Exterior for detailed information on the safe handling of the product.

- Long-lasting and smooth finish
- Protects your walls from dirt, dust, and harsh weather
- Waterproof to safeguard walls against dampness
- Easy to apply and dries quickly
- Retentions the color
- Multiple uses, including walls, bricks, and metals

### ADDING COLOR TO YOUR SPACE FOR OVER A DECADE!

- Professional Service
- Premium-quality paint
- Value for money

### PACKING SIZE AVAILABLE

- 1 Ltr, 4 Ltr, 10 Ltr, & 20 Ltr







## CREATE A PERFECT FINISH WITH PARAMOUNT SHINE ACRYLIC EMULSION EXTERIOR

### TECHNICAL SPECIFICATION

PROPERTY	TYPICAL
Covering	On normal masonry surface brush applied: Single Coat: 10.5-11.5 SqMt/Lt at recommended DFT Double Coats: 5.5-6 SqMt/Lt at recommended DFT
Drying Time	Touch Dry 1 hr   Recoat : 4-6 hrs
Recommended Dry Film Thickness (DFT)	On normal masonry surface brush applied: Single Coat: 10.5-11.5 SqMt/Lt at recommended DFT Double Coats: 5.5-6 SqMt/Lt at recommended DFT
Weight per Liter	1.25+/-0.05
Gloss / Sheen Level	0-9 on glass plate at 60°, smooth finish with slight sheen
Viscosity	106KU+/- 2
PH	8 to 9
Shelf Life	Minimum 1 yr when stored in original sealed container away from sunlight and excessive heat
Pot Life	24 hrs
Thinning	40-45% by volume with water
Packing Size Available	1 Ltr, 4 Ltr, 10 Ltr, & 20 Ltr

### APPLICATION

- It is used to protect the exterior walls of buildings and other structures from the elements.
- To enhance the aesthetic appeal of exteriors, they come in a variety of colors and finishes.
- To protect the structure from the effects of UV radiation, water, and pollution.
- To protect surfaces from mold and mildew.
- To help reduce energy costs, as they reflect the heat of the sun away from the building.

### FEATURES

**Durability:** Highly durable and can last up to 10 years with proper maintenance.

**Weatherproof:** Weatherproof and provides protection against extreme weather conditions like heavy rains and strong sunshine.

#### ADDING COLOR TO YOUR SPACE FOR OVER A DECADE!

Corporate office - Om Plaza, First Floor, 7-Krishna Vihar Govindpuri, Sachin Tendulkar Marg, Gwalior (M.P.)-474011  
Plant - TIWH, Purani Chawani, Gwalior

