



Pride of Walls



CREATE A PERFECT FINISH WITH **PARAMOUNT SHINE** ACRYLIC INTERIOR EMULSION

PRODUCT DESCRIPTION

Paramount Shine Acrylic Emulsion - Interior is a 100% pure acrylic emulsion that offers superb bacterial and UV resistance. It is a reliable and enduring coating, specifically formulated to bear the harsh weather conditions of high rain, high temperatures and high humidity. It can be used on a wide range of Interior surfaces such as cement plaster, masonry, concrete, asbestos sheet, POP Gypsum, etc.

SURFACE PREPARATION

PLASTER

It is essential that newly constructed masonry surfaces have a minimum curing period of 28 days before any further application. It is also recommended that a base coat of Paramount Interior Emulsion and Interior primer be applied before using Interior Emulsion for optimal results.

CLEANING

The surface must be free from any dirt, oil, grease and other impurities. All loose material should be removed using a scraper or a stiff wire brush. Any dampness on the wall should be treated accordingly.

FILLING CRACKS, HOLES AND DENTS

For repairing cracks up to 3 mm, holes and dents, mix Paramount Shine Wall Putty or white cement with fine sand in a 1:3 ratio. If the interior surface or substrate is regularly exposed to moisture or dampness, ensure the repairs are done prior to application.



PRECAUTION

Do not over-dilute or over-extend the brush. Stir Well Before Use.

POST PAINTING CARE

For performance optimization ensure proper washing and cleaning of structures at regular intervals.

HANDLING AND STORAGE

Keep containers airtight during handling and storage to avoid loss of material. Store Paramount Shine Interior Emulsion Paint in a cool dry place and also protect it from extreme climatic conditions during storage, in transit and at the site.

SAFETY

Please refer to the detailed MSDS of Paramount Shine Acrylic Emulsion - Interior for detailed information on the safe handling of the product.

- Long-lasting and smooth finish
- Protects your walls from dirt, dust, and harsh weather
- Waterproof to safeguard walls against dampness
- Easy to apply and dries quickly
- Retentions the color
- Multiple uses, Including walls, bricks, and metals

ADDING COLOR TO YOUR SPACE FOR OVER A DECADE!

- Professional Service
- Premium-quality paint
- Value for money

PACKING SIZE AVAILABLE

1 Ltr, 4 Ltr, 10 Ltr, & 20 Ltr





Pride of Walls



CREATE A PERFECT FINISH WITH PARAMOUNT SHINE ACRYLIC INTERIOR EMULSION

TECHNICAL SPECIFICATION

PROPERTY	TYPICAL
Covering	On normal masonry surface brush applied: Single Coat: 10.5-11.5 SqMt/Lt at recommended DFT Double Coats: 5.5-6 SqMt/Lt at recommended DFT
Drying Time	Touch Dry 1 hr Recoat: 4-6 hrs
Recommended Dry Film Thickness (DFT)	On normal masonry surface brush applied: Single Coat: 10.5-11.5 SqMt/Lt at recommended DFT Double Coats: 5.5-6 SqMt/Lt at recommended DFT
Weight per Liter	1.25+/-0.05
Gloss / Sheen Level	0-9 on glass plate at 60°, smooth finish with slight sheen
Viscosity	106KU+/-2
PH	8 to 9
Shelf Life	Minimum 1 yr when stored in original sealed container away from sunlight and excessive heat
PACKING SIZE AVAILABLE	1 Ltr, 4 Ltr, 10 Ltr, & 20 Ltr

FEATURES

Durability: Highly durable and can last up to 10 years with proper maintenance.

Weatherproof: Weatherproof and provides protection against extreme weather conditions like heavy rains and strong sunshine.

ADDING COLOR TO YOUR SPACE FOR OVER A DECADE!

Corporate office - Om Plaza, First Floor, 7-Krishna Vihar Govindpuri, Sachin Tendulkar Marg, Gwalior (M.P.)-474011
Plant - TIWH, Purani Chawani, Gwalior

APPLICATION

- It is used to protect the Interior walls of buildings and other structures from the elements.
- To enhance the aesthetic appeal of Interior, they come in a variety of colors and finishes.
- To protect the structure from the effects of UV radiation, water, and pollution.
- To protect surfaces from mold and mildew
- To help reduce energy costs, as they reflect the heat of the sun away from the building.

